

1233

## Digality 4/1+1 DiSEqC switch+combiner

### PRODUCT VISUAL



### PRODUCT DESCRIPTION

The Digality 4/1+1 is suited for selection of 2 and/or 4 satellite systems (e.g. ASTRA + Eutelsat) and the terrestrial signals with one satellite receiver.

### FEATURES

- Switching to different inputs by DiSEqC-commands - Position and Option
- The switch do not need an additional power supply unit
- The switch are suited for LNBF's and broadband LNB's
- UV-resistant waterproofed box for outdoor installation incl. cable clip for mast installation is included

### TECHNICAL SPECIFICATIONS

#### Frequency area

Sat.: 4 x 950 - 2400 MHz

Terr.: 47 - 862 MHz

#### DiSEqC-control

DiSEqC 2.0

#### Linearity

± 1 dB

#### Functions

Position / Option

#### Through loss

Sat.: 2.5 dB

Terr.: 0.5 dB

#### Return loss

> 12 dB

#### DC loop through

700 mA

#### Isolation

> 30 dB

#### Current consumption

< 30 mA

#### Dimensions (WxHxD)

90 x 45 x 18 mm / 105 x 45 x 75 mm

#### Weight

141 g

#### Operating temperature

-30° C ~ 60° C